

# Moonstruck

12x24 Porcelain



03AV3011224H (honed)  
03AV3011224U (unpolished)



03AV3021224H (honed)  
03AV3021224U (unpolished)



03AV3031224H (honed)  
03AV3031224U (unpolished)



03AV3041224H (honed)  
03AV3041224U (unpolished)



03AV3051224H (honed)  
03AV3051224U (unpolished)



Tile: 12x24 - 18x36

Mosaic: N/A

Trim: 4x24 Bullnose

For more information  
and images:



## Technical Characteristics

Test Item	Test Method	Test Result
Breaking Strength	ASTM C648	> 500 lbf
Bond Strength	ASTM C482	> 200 psi
Chemical Resistance	ASTM C650	<b>Unaffected</b>
Frost Resistance	ASTM C1026	<b>Resistant</b>
Water Absorption	ASTM C373	< 0.20%
Scratch Hardness	Mohs Scale	7
DCOF	AcuTest	<b>0.42-0.52 (Honed); 0.50-0.60 (Unpolished)</b>

Nominal Size	Actual Size	Thickness	Finish	Rectified
12" x 24"	11.69" x 23.5"	10.5 mm	Honed or Unpolished	Yes
18" x 36"	17.6" x 35.31"	10.5 mm	Honed or Unpolished	Yes
4" x 24" Bullnose	3.78" x 23.5"	10.5 mm	Honed or Unpolished	-

Installation Note: The TCNA recommends rectangular shape tile be installed with maximum of 33% offset in order to resolve any possible lippage from one tile to the next.

