

Ready To Wear

12x24 Porcelain

mosaic 
Products. Design. Solutions.



03AV3111224U



03AV3121224U



03AV3141224U



03AV3161224U



03AV3131224U



03AV3151224U



03AV3171224U



03AV3181224U



Tile: 2x6 - 12x24
Mosaic: N/A
Trim: 4x24 Bullnose

For more information
and images:



Technical Characteristics

Test Item	Test Method	Test Result
Breaking Strength	ASTM C648	> 450 lbf
Bond Strength	ASTM C482	> 200 psi
Chemical Resistance	ASTM C650	Unaffected
Frost Resistance	ASTM C1026	Resistant
Water Absorption	ASTM C373	< 0.20%
Scratch Hardness	Mohs Scale	7
DCOF	AcuTest	0.50-0.60

Nominal Size	Actual Size	Thickness	Finish	Rectified
2" x 6"	1-13/16" x 15-13/16"	3/8"	Unpolished	-
12" x 24"	11-13/16" x 23-13/16"	3/8"	Unpolished	-
4" x 24" Bullnose	3-13/16" x 23-13/16"	3/8"	Unpolished	-

Installation Note: The TCNA recommends rectangular shape tile be installed with maximum of 33% offset in order to resolve any possible lippage from one tile to the next.

