Civilization Porcelain Stone®

Sizes (Available in all colors)







2 x 2 Square Mosaic (Mounted on a 298 x 298 mm sheet)



Polygon Mosaic (Mounted on a 341 x 385 mm sheet)

Sizes	&	Fin	ishe
	-		

Sizes & Finishes				
Field Tile - Rectified		1	Available in all colors	
Nominal (in)	Actual (mm)	Thickness (mm)	Grout Joint (mm)	Finish
12 x 24	297 x 597	9.5	3	UPS/SPO
24 x 24	597 x 597	9.5	3	UPS/SPO
24 x 48	597 x 1197	10.5	3	UPS/SPO

Note: Field tile is rectified with a 3mm grout joint

Mosaics		1	Available in all colors	
Nominal (in)	Sheet Size (mm)	Thickness (mm)	Grout Joint (mm)	Finish
2 x 2 Mosaic*	298 x 298	9.5	3	UPS
Polygon Mosaic	341 x 385	9.5	2	UPS

* Mounted on 12 x 12 sheet

Coordinating Trim			Available in all colors	
Nominal (in)	Actual (mm)	Thickness (mm)	Grout Joint (mm)	Finish
4 x 24 Single Bullnose	97 x 597	9.5	3	UPS/SPO
6 x 12 Cove Base	150 x 297	9.5	3	UPS

4 x 24 Single Bullnose

l		
6 x	12 Cove Ba	ase

Product Performance		
Breaking Strength	≥450 lbf	ASTM C648
Bond Strength	>200 psi	ASTM C482
Chemical Resistance	Unaffected	ASTM C650
Frost Resistance	Resistant	ASTM C1026
Water Absorption	<0.50%	ASTM C373
Scratch Hardness	7	Mohs Scale

Wet Dynamic Coefficient of Friction Range

	0	
UPS	0.50 - 0.60	ANSI A326.3
SPO	0.42 - 0.52	ANSI A326.3

Get Planked!

Our Porcelain Stone[®] products are available in popular plank shapes with no minimum order and quick fulfilment. See website for more details and sizes.



Shade & Texture Index

Civilization has a shade variation of V3.



V1 Uniform appearance V2 Slight Variation **V3 Moderate Variation** V4 Substantial Variation

This porcelain tile product is produced with a V3 variation. While the colors and/or textures present on a single piece of tile will be indicative of the colors and/or textures to be expected on the other tiles, the amount of colors and/or texture on each piece may vary significantly. It is recommended that the range be viewed before selection.



Civilization

Crossville, Inc.

PO Box 1168 Crossville, TN 38557
 Phone
 931.484.2110

 Fax
 931.456.2956

 E-Mail
 Crossc@CrossvilleInc.com

 Web
 CrossvilleInc.com

Application Areas

Finish	Interior Floors (dry)	Interior Walls (wet/dry)	Exterior Walls	Interior Floors (Standing water/ shower floors)	Exterior/Paving	Pool/Fountain Full Lining**	Water Line Pool/ Fountains
UPS	\checkmark	√ *	~			\checkmark	\checkmark
SPO	\checkmark		\checkmark			\checkmark	\checkmark

** Excludes mesh mounted mosaics. Crossville recommends face mounted or edge mounted mosaics for fully submerged applications. Contact your Crossville sales representative for more information. NOTE: Trim applications will differ from field tile applications for the same series. For more information on ANSI- A362.3 visit our website at

https://www.crossvilleinc.com/Resources/Tile-101/DCOF?tab=1

Recommended Use

Civilization UPS is recommended for interior floors, interior walls, countertops, exterior walls, pool waterlines and full linings[†] in both residential and commercial applications. Civilization is not recommended for exterior horizontal surfaces or exterior paving. **The semi-polished (SPO) field tile is not recommended for wet areas where standing water may occur.** See CrossvilleInc.com for detailed installation instructions.

+ Excludes mesh mounted mosaics.

Wet area use for Civilization Mosaics

Crossville[®] produces the Civilization 2 x 2 and Polygon mosaics with the Cross-Sheen (UPS) finish. The ANSI A326.3 wet Dynamic COF of Civilization is ≥0.42. Their small sizes ensure frequent grout joints which provides traction and drainage. Crossville cannot control situations involving incorrect installation, improper slope to the drain for elimination of standing water and poor surface cleaning.

This information is provided so that customers may make a realistic and informed decision when comparing Civilization to other tile products in wet area environments, such as residential/commercial bathrooms, showers, and interior pool decks.

Care and Maintenance

Regular cleaning is the best way to keep Civilization tile looking good for years to come. Use clean, hot water (combined with a household cleaner for more aggressive cleaning). Rinse thoroughly and dry with a soft cloth. No waxes are needed. More information regarding the care and maintenance of Crossville[®] products is available at Crossvillelnc.com.

Our Warranty

Crossville Inc. guarantees that its products will meet or exceed the performance specifications outlined in ANSI A137.1- 2022 and in the performance data section of the Crossville, Inc. general product catalog. For complete details check our website at CrossvilleInc.com.

Information listed here is subject to change. Please refer to CrossvilleInc.com for the latest, most accurate information.

>>> Crossville[®] Sample Express

Visit the website to learn more: CrossvilleInc.com/Products/ Civilization

Loose Tile Samples

Sizes may vary depending on product series Max. of 4 large field tile per order

Standard Shipping FedEx Ground

CrossvilleInc.com

If you want a better idea of what Crossville tile would look like in a particular room setting, simply visit our website and click on Cross-Vision. This powerful software tool allows you to visualize different types of Crossville tile. In addition, you'll find comprehensive information about Crossville's entire portfolio of products. You can also learn about the latest styles and trends from industry experts, download detailed care and maintenance instructions. for our various products, or browse electronic versions of Crossville's product brochures. So whether you need information about Crossville products or tile in general, please visit us at CrossvilleInc.com. Information listed here is subject to change.

Trade Organizations





Environmentally Aware







