Element

12x24 Color Body Porcelain









15ELESIL1224



15ELEGRA1224



2x2 Mosaic



Brick Mosaic



Turtle Mosaic



15ELEEAR1224




15ELECAR1224



Tile: 12x24

Mosaics: 2x2 - 3x6 Brick - 13x15 Turtle

Trim: 3x24 Bullnose - 6x12 Cove Base



Element Color Body Porcelain













Technical Characteristics

Characteristic	Test Method	Calibrated		Rectified		
		Minimum	Maximum	Minimum	Maximum	- Value
Nominal Size	ASTM C499	- 3%	+ 3%	- 3%	+ 2%	Compliant
Caliber Range		- 0.5% or - 0.08 in	+ 0.5% or + 0.08 in	- 0.25% or - 0.03 in	+ 0.25% or + 0.03 in	Compliant
Thickness		N/A	Range: 0.40 in	N/A	Range: 0.40 in	Compliant
Wedging	ASTM C502	- 0.5% or - 0.08 in	+ 0.5% or + 0.08 in	- 0.25% or - 0.03 in	+ 0.25% or + 0.03 in	Compliant
Warpage Edge	ASTM C485	- 0.75% or - 0.09 in	+ 0.75% or + 0.09 in	- 0.40% or - 0.05 in	+ 0.40% or + 0.05 in	Compliant
Warpage Diagonal		- 0.5% or - 0.08 in	+ 0.5% or + 0.08 in	- 0.40% or - 0.07 in	+ 0.40% or + 0.07 in	Compliant
		All Porcelain Tiles				
Water Absorption	ASTM C373	≤ 0.5%				≤ 0.5%
Breaking Strength	ASTM C648	Average ≥ 250 lbf; Individual ≥ 225 lbf				≥ 350 lbf avg
Bond Strength	ASTM C482	≥ 50 psi				≥ 100 psi
Resistance to Freeze/ Thaw Cycling	ASTM C1026		Resistant			
Chemical Resistance	ASTM C650		Unaffected			
Stain Resistance	ASTM C1378	As Reported				Unaffected
Dynamic Coefficient of Friction	DCOF (Wet)	Requires a r	> 0.42			
VOC	No VOC					

Size	Nominal Size	Thickness	Finish	Rectified
12" x 24"	11-3/4" x 23-5/8"	9 mm	Matte	-
2" x 2" Mosaic	11-3/4" x 11-3/4"	9 mm	Matte	-
2.9" x 5.8" Brick Mosaic	11-3/4" x 11-3/4"	9 mm	Matte	-
13" x 15" Turtle Mosaic	13-3/8" x 15-1/4"	9 mm	Matte	-
3" x 24" Bullnose	2-7/8" x 23-5/8"	9 mm	Matte	-
6" x 12" Cove Base	5-7/8" x 11-3/4"	8.5 mm (7 mm flat part)	Matte	-

Installation Note: The TCNA recommends rectangular shape tile be installed with maximum of 33% offset in order to resolve any possible lippage from one tile to the next.

