

Road

12x24 Color Body Glazed Porcelain

mosaic 
Products. Design. Solutions.



15ROAWHI1224




15ROAIVO1224



15ROAGRA1224



15ROABLA1224



15ROAWHI2M



15ROAIVO2M



15ROAGRA2M



15ROABLA2M



QuickSHIP (noted color only)

Tile: 12x24

Mosaic: 2x2

Special Order

Tile: 12x24

Mosaics: 2x2

Trim: 3x24 Bullnose

For more information
and images: 

Road

12x24 Color Body Glazed Porcelain



Technical Characteristics

		Porcelain Tile Specification				Value	
Characteristic	Test Method	Calibrated		Rectified			
		Minimum	Maximum	Minimum	Maximum		
Nominal Size	ASTM C499	- 3%	+ 3%	- 3%	+ 2%	Compliant	
Caliber Range		- 0.5% or - 0.08 in	+ 0.5% or + 0.08 in	- 0.25% or - 0.03 in	+ 0.25% or + 0.03 in	Compliant	
Thickness		N/A	Range: 0.4 in	N/A	Range: 0.4 in	Compliant	
Wedging	ASTM C502	- 0.5% or - 0.08 in	+ 0.5% or + 0.08 in	- 0.25% or - 0.03 in	+ 0.25% or + 0.03 in	Compliant	
Warpage Edge	ASTM C485	- 0.75% or - 0.09 in	+ 0.75% or + 0.09 in	- 0.40% or - 0.05 in	+ 0.40% or + 0.05 in	Compliant	
Warpage Diagonal		- 0.5% or - 0.08 in	+ 0.5% or + 0.08 in	- 0.40% or - 0.07 in	+ 0.40% or + 0.07 in	Compliant	
All Porcelain Tiles							
Water Absorption	ASTM C373	≤ 0.5%				≤ 0.5%	
Breaking Strength	ASTM C648	Average ≥ 250 lbf; Individual ≥ 225 lbf				Compliant	
Surface Abrasion Resistance	ASTM C1027	As Reported				Class IV	
Resistance to Freeze/Thaw Cycling	ASTM C1026	As Reported				Resistant	
Chemical Resistance	ASTM C650	As Reported				Unaffected	
Stain Resistance	ASTM C1378	As Reported				Unaffected	
Dynamic Coefficient of Friction	DCOF (Wet)	Requires a minimum value of 0.42 for commercial areas that are likely to be wet				> 0.42	
VOC	No VOC						

Nominal Size	Actual Size	Thickness	Finish	Rectified
12" x 24"	11-3/4" x 23-5/8"	8 mm	Matte	-
2" x 2" Mosaic	11-3/4" x 11-3/4"	8 mm	Matte	-
3" x 24" Bullnose	2-7/8" x 23-5/8"	8 mm	Matte	-

All tile is subject to variations in technical specifications and performance due to the inherent variables in the raw materials and production process. It is understood that test results on a particular product may vary slightly from tile to tile and from test to test. Test results are not guarantees of minimum or maximum thresholds of performance.



For your convenience, select products are stocked in our Central Service Center.

mosaic 
Products. Design. Solutions.