

Lumber

6x24 Glazed Porcelain



70LUMGRA24



QuickSHIP

Tile: 6x24

Mosaic: N/A

Trim: N/A

* Limited Inventory – Available only while QS stock lasts*

For more information
and images:





Technical Characteristics

Reference	Characteristic	Test Method	Required Values		Value	
Dimensional Standard	Calibrated	Nominal Size	ASTM C499	± 3%		Comply
		Caliber Range	ASTM C499	± 0.5%	± 0.08 in	Comply
		Warpage Edge	ASTM C485	± 0.5%	± 0.07 in	Comply
		Warpage Diagonal	ASTM C485	± 0.5%	± 0.07 in	Comply
		Wedging	ASTM C502	± 0.5%	± 0.08 in	Comply
	Rectified	Nominal Size	ASTM C499	- 3%	+ 2%	Comply
		Caliber Range	ASTM C499	± 0.25%	± 0.03 in	Comply
		Warpage Edge	ASTM C485	± 0.4%	± 0.05 in	Comply
		Warpage Diagonal	ASTM C485	± 0.4%	± 0.07 in	Comply
		Wedging	ASTM C502	± 0.25%	± 0.03 in	Comply
Mechanical Standard	Thickness	ASTM C499	± 0.040 in		Comply	
	DEEP Abrasion	ASTM C1243	< 175mm ³		~ 40 mm ³	
	Bond Strength	ASTM C482	≥ 50 psi		Comply	
	Water Absorption	ASTM C373	Maximum 0.5%		~ 0.13%	
	Thermal Shock Resistance	ASTM C484	Pass		Comply	
	Chemical Resistance	ASTM C650	Pass		Class A	
	Stain Resistance	ASTM C1378	Pass		Class A	
	Breaking Strength	ASTM C648	≥ 275 lbf		Comply	
	Resistance to Freeze / Thaw Cycling	ASTM C1026	As Reported		Comply	
	Scratch Hardness	Mohs	Declared Value		Mohs ≥ 6	
	Fire Reaction - Floor	EN 13823	Not Required		A1fl class (No reaction)	
	Fire Reaction - Wall	EN 13823	Not Required		A1 class (No reaction)	
	VOC	No VOC				
Dynamic Coefficient of Friction DCOF	ANSI A326.3	≥ 0.42 Wet		0.54		

Nominal Size	Actual Size	Thickness	Rectified
6" x 24"	5.91" x 23.62"	8.5 mm	-

Installation Note: Due to its linear plank shape, this material requires particular care when it comes to installation. The tile will look its best when offset is less than 33%. The staggered installation will minimize lippage which is common in tiles of this format. No claim will be honored after installation.



For your convenience, select products are stocked in our Central Service Center.