

Utopia

12x24 Ceramic



74UTOBON1224



74UTOGRA1224




74UTOOXF1224



74UTOBON2M



74UTOGRA2M



74UTOOXF2M



QuickSHIP

Tile: 12x24 - 13x13

Mosaic: 2x2

Trim: N/A

Recommended Jolly Edge Trim:

12x24 - 3/8" A100 / 13x13 - 5/16" A80

UTOBON - White

UTOGRA - Gray

UTOOXF - Classic Gray

For more information
and images:



Technical Characteristics

Test Item	Test Method	Test Result
Warpage Diagonal	ASTM C485	670.8 mm ±0.5%
Warpage Edge	ASTM C485	600.1 mm ±0.5%
Water Absorption	ASTM C373	3 < wa ≤ 6.0
Breaking Strength	ASTM C648	≥ 250 lbf
Visible Abrasion Resistance	ASTM C1027	PEI IV (BON, GRA); III (OXF)
Thermal Shock Resistance	ASTM C484	Resistant
Crazing Resistance	ASTM C424	Resistant
Frost Resistance	ASTM C1026	Resistant
Dynamic Coefficient of Friction	ANSI A137-1	≥ 0.42
Chemical Resistance	ASTM C650	Class A Resistant
Stain Resistance	ASTM C1378	Class A

Nominal Size	Actual Size	Thickness	Finish	Rectified
12" x 24"	11.81" x 23.62"	10.5 mm	Matte	-
13" x 13"	-	-	Matte	-
2" x 2" Mosaic	11.75" x 11.75"	10.5 mm	Matte	-

Installation Note: The TCNA recommends rectangular shape tile be installed with maximum of 33% offset in order to resolve any possible lippage from one tile to the next.



For your convenience, select products are stocked in our Central Service Center.