

# Gard Stone

12x24 Glazed Porcelain



75GARWHI1224



75GARLIG1224



75GARGRA1224



75GARWHI2M



75GARLIG2M



75GARGRA2M



**QuickSHIP** (noted colors only)

Tile: 12x24

Mosaic: 2x2

Recommended Jolly Edge Trim:  
3/8" A100 Aluminum

*Non-QuickSHIP items are available for commercial projects only. Inquire with a sales representative for additional information.*

Tile: 12x24 - 24x48

Trim: 4x12 Bullnose

For more information and images:





## Technical Characteristics

Test Item	Test Method	Test Result
Breaking Strength	ASTM C648-04	≥ 330 lbs.
Chemical Resistance	ASTM C650-04	Class A
Abrasion Resistance	ASTM C1027	Class IV
Stain Resistance	ASTM C1378-04	Class A
Scratch Hardness	MOH'S	7
Water Absorption	ASTM C373-16	< 0.5%
DCOF (Wet)	ANSI A326.3	≥ 0.42

Nominal Size	Actual Size	Thickness	Finish	Rectified
12" x 24"	11.81" x 23.62"	8.2 mm	Matte	-
24" x 48"	23.62" x 47.24"	9.0 mm	Matte	Yes
2" x 2" Mosaic	11.81" x 11.81"	8.2 mm	Matte	Yes
4" x 12" Bullnose	4.0" x 11.75"	8.2 mm	Matte	Yes

All tile is subject to variations in technical specifications and performance due to the inherent variables in the raw materials and production process. It is understood that test results on a particular product may vary slightly from tile to tile and from test to test. Test results are not guarantees of minimum or maximum thresholds of performance.

Installation Note: The TCNA recommends rectangular shape tile be installed with maximum of 33% offset in order to resolve any possible lippage from one tile to the next.



For your convenience, select products are stocked in our Central Service Center.