

# Silvanus

24x24 Porcelain



75SILCOH24



75SILROY24



Tile: 24x24  
Mosaics: N/A  
Trim: N/A

For more information  
and images:





## Technical Characteristics

Test Item	Test Method	Test Result
Breaking Strength	ASTM C648	≥ 425 lbs.
Scratch Hardness	MOH'S	7
Chemical Resistance	ASTM C650-04	<b>Class E</b>
Abrasion Resistance	ASTM C1027	<b>Class IV</b>
Thermal Shock Resistance	ASTM C484	<b>Resistant</b>
Frost Resistance	ASTM C1026	<b>Resistant</b>
Water Absorption	ASTM C373	≤ 0.5%
DCOF (Wet)	ASTM C1028	≥ 0.42
Category of Use	ANSI A326.3	<b>IW</b>

Nominal Size	Actual Size	Thickness	Finish	Rectified
24" x 24"	23.56" x 23.56"	9.0 mm	Matte	Yes

All tile is subject to variations in technical specifications and performance due to the inherent variables in the raw materials and production process. It is understood that test results on a particular product may vary slightly from tile to tile and from test to test. Test results are not guarantees of minimum or maximum thresholds of performance.

Installation Note: The TCNA recommends rectangular shape tile be installed with maximum of 33% offset in order to resolve any possible lippage from one tile to the next.