



78GROBLO2448R



78GROSUN2448R



QuickSHIP (48 Hours)

Tile: 24x48 Ribbed

For more information  
and images:



## Technical Characteristics

Test Item	Test Method	Test Result
Water Absorption	ISO 10545-3	< 0.5%
Breaking Strength	ISO 10545-4	≥ 43 N/mm <sup>2</sup>
Surface Abrasion Resistance	ISO 10545-7	PEI 5
Thermal Shock Resistance	ISO 10545-9	Guaranteed
Frost Resistance	ISO 10545-12	Guaranteed
Chemical Resistance	ISO 10545-13	GA (V); GLA (V); GHA (V)
Stain Resistance	ISO 10545-14	Compliant
Dynamic Coefficient of Friction	DCOF	> 0.42
Slip Resistance	EN 16165 Annex B EN 16165 Annex A	R10; A+B

Nominal Size	Actual Size	Thickness	Rectified
24" x 48"	23.50" x 47.13"	9 mm	Yes

Values reflect an average among tests performed in the manufacturer's laboratory according to the standard requirements and/or through a third party laboratory. Tests are performed on actual production, first choice material. Values may vary between single individual production runs.

Installation Note: The TCNA recommends rectangular shape tile be installed with maximum of 33% offset in order to resolve any possible lippage from one tile to the next.



For your convenience, select products are stocked in our Central Service Center.